

CLAIM AMENDMENTS

1. (Currently Amended)

Drive A drive device comprising: a rolling-body screw mechanism having an axis of rotation; a housing divided into two housing parts transversely to the axis of rotation of the screw mechanism; a hollow rotor mounted rotatably on a spindle nut of the screw mechanism; a threaded spindle of the rolling-body screw mechanism mounted rotatably on the spindle nut of the rolling-body screw mechanism, the spindle nut being drive-connected to the rotor; and a rolling mounting means for rotatably mounting the rolling-body screw mechanism in the housing provided on only one housing part of the housing, wherein the rolling mounting means is formed by a multi-row angular ball bearing having an outer ring seated in a housing bore of the one housing part, and wherein ball grooves of the angular ball bearing are formed directly on an outer circumference of the spindle nut, and wherein the mounting means is positioned with respect to the spindle nut to receive all of the loading there from in a cantilevered manner.

2. (Previously Canceled)

3. (Previously Canceled)

4. (Currently Amended)

Drive The drive device according to Claim 1, wherein the rolling mounting means is arranged axially within a construction space occupied by the spindle nut.

5. (Currently Amended)

Drive The drive device according to Claim 1, wherein the rotor is arranged axially within a construction space occupied by the spindle nut.

6. (Currently Amended)

Drive The drive device according to Claim 1, wherein the rolling-body screw mechanism is a ball screw mechanism with an outer deflection for balls of the ball screw mechanism.

7. (Currently Amended)

Drive The drive device according to Claim 4, wherein the rolling body screw mechanism is a ball screw mechanism with an outer deflection for balls, and

the spindle nut is provided, in a region radially between the threaded spindle and the rolling mounting means, with a return bore for balls of the ball screw mechanism.

8. (Currently Amended)

Drive The drive device according to Claim 1, wherein the rotor is provided with a driving surface for the drive belts ~~on the circumference of the rotor.~~

9. (New Claim)

A drive device comprising: a rolling-body screw mechanism having an axis of rotation; a housing divided into two housing parts transversely to the axis of rotation of the screw mechanism; a hollow rotor mounted rotatably on a threaded spindle nut of the screw mechanism; a threaded spindle of the rolling-body screw mechanism mounted rotatably on the spindle nut of the rolling-body screw mechanism, the spindle nut being drive-connected to the rotor at a position that is axially displaced from the threads of the spindle nut; and a rolling mounting means for rotatably mounting the rolling-body screw mechanism in the housing provided on only one housing part of the housing, wherein the rolling mounting means is formed by a multi-row angular ball bearing having an outer ring seated in a housing bore of the one housing part, and wherein ball grooves of the angular ball bearing are formed directly on an outer circumference of the spindle nut.